



Heraklith M

Universal plaster base



Heraklith M

Wood wool board according to EN 13168
WW-EN 13168-L1-W1-T1-S1-P1-CS(10/Y)200 CI 3

Description of Product:

- Mineral bound Wood Wool insulation board

Purpose of use:

- For concreting in
- Underground for different plaster, fixed on wood panels

Advantages:

- Fire resistant
- Ideal underground for plaster

Notes:

- Please observe the relevant processing guidelines. In addition, the relevant standards and the recognised rules of technology apply.

Technical data

Thickness	mm	8	15
Weight	kg/m ²	5,5	7,5
Length	mm	2000	1000
Width	mm	500	600

Form of delivery: palletised

Characteristics	Symbol	Description / Data	Unit	Standard	Level acc. EN 13168
Fire behaviour	--	B-s1, d0	--	EN 13501-1	
Thickness	d	8 15	[mm]	EN 13168	
Nominal thermal conductivity	λ_D	0,080	[W/mK]	EN 13168	
Nominal thermal insulation resistance	R _D	0,10 0,15	[m ² K/W]	EN 13168	
Bending strength	σ_{10}	≥ 200	[kPa]	EN 13168	CS(10/Y)200
Width tolerance		± 3	[mm]	EN 13168	W1
Thickness tolerance		+ 3 / -2	[mm]	EN 13168	T1
Water vapour diffusion resistance coefficient	μ	5	[--]	EN 13168	
Specific thermal capacity	c	≥ 1,47	[kJ/kgK]	ÖNORM B 8110-7	

Sale via the specialist trade.



Institut für Bauen
und Umwelt e. V.

The values in this product data sheet correspond to the present state of development of our products and become invalid on the publication of a new version. Always make sure that you use the latest version of this information. The suitability of the product is not binding for individual cases of a special nature. Our General Terms of Sale, Delivery and Payment apply exclusively. All data are included without warranty. We reserve the right to make modifications.
Stand: 04/2014 li-jb (ersetzt 07/2013 li-jb)

Heraklith® is registered trademark of **KNAUF INSULATION**

Knauf Insulation GmbH
Industriestraße 18
A-9586 Fürnitz
Telefon +43 4257 3370-0
Telefax +43 4257 3370-2300
www.knaufinsulation.at